

AGLAIA FURNITURE WAX

Fragrant natural wax ointment for care and protection of oiled wood surfaces indoors such as furniture, toys and formwork. Exclusively from natural raw materials.



Ranges of Application:

AGLAIA FURNITURE WAX is a fragrant transparent wax ointment providing a velvety shine when dry and buffed. Suitable for upgrading wood furniture, racks or toys. Also for planed formwork or paneling. Soft and easy-use. Ideal for manual application on smaller surfaces, using a rolled-up cloth. Oil raw woods to saturation beforehand, see Surface and Pretreatment. Recommended for high traffic floors: AGLAIA LIQUID WAX.

Processing:

Apply AGLAIA FURNITURE WAX extremely sparingly with a non-fraying rag or rolled-up cloth. Distribute well and evenly. After drying for about 12 to 24 hours, buff carefully and evenly with a rag, a rolled-up cloth or a buffing pad to obtain a silky shine.

Technical Features:

AGLAIA LIQUID WAX contains nothing but animal and plant waxes, mixed with pure essential oils. Careful buffing produces a very thin, silky, pleasant-to-touch wax film. No static build-up, therefore virtually no dust attraction. When applied sparingly, easy-care and dirt-repellent. Despite increased water-repellent properties, not suitable for use in areas with splash water. Surfaces oiled and waxed with purely natural products are highly recommended from a biological and ecological building point of view as they provide an agreeable room climate. The diffusion and absorption capacities of unsealed wooden surfaces remain unaffected.

Physical/Technical Characteristics:

Density: 0.9 g/cm³
Viscosity: at room temperature: pasty

Color tone:

Transparent

Drying:

Touch dry after 60 minutes. Can be carefully buffed after about 12 to 24 hours. Do not wax freshly oiled surfaces sooner than 24 to 48 hours later.

Yield:

Approx. 0.03 to 0.05 l per application and m².

Available Sizes:

0.1 l and 0.5 l.

Cleaning:

Clean appliances, tools and clothes with AGLAIA BAL-SAM LACQUER THINNER.

Storage:

Lasts at least 18 months when stored cool and free of frost in the airtight sealed original container. Once opened, re-seal airtight.

Composition:

Full declaration according to the quality standards of the Association for Natural Colors (AGN):

[1]: Yellow beeswax, Citrus peel oil; [2]: Carnauba wax.

Explanation of Symbols:

- [1] ... Raw material rate in product > 10%
- [2] ... Raw material rate in product 1-10%
- [3] ... Raw material rate in product < 1%

AGLAIA FURNITURE WAX

Surface and Pretreatment:

General Requirements:

The surface must be clean, dry, solid and coatable. Maximum wood moisture: 12 % for hardwood, 15 % for conifer wood. Thoroughly remove thick, dirty wax layers and grease or resin remainders with AGLAIA BALSAM LACQUER THINNER. Also make samples before applying to wood containing a substantial amount of tannic acid, oils or resins in particular oak or tropical woods and wood based materials because of possible discoloration and substances that may delay the drying process.

The interior of closets, drawers and chests should be primed using AGLAIA WOOD IMPREGNATION PRIMER only.

Pretreatment:

Suitable for an oil or wax treatment are planed, fine-sanded facing woods with an attractive grain pattern. Fine-sand (grit 240 or finer) any protruding fibers after priming. Highest surface quality through repeated wetting and fine-sanding of the surface.

Oil priming:

AGLAIA PORE FILLER is suitable for a saturating, water-repellent priming of wood. Economic, easy-use and especially attractive on figured conifer wood due to its color intensifying, „grain-raising“ effect. AGLAIA RESIN OIL PROTECTION is a solvent-free alternative, virtually non-yellowing and not significantly enhancing grain and pattern. Make sure to apply very carefully and excess-free with a rolled-up cloth. Extremely hard-wearing and abrasion-resistant when dry. For light colored, untreated woods not subject to strain, AGLAIA WOOD IMPREGNATION PRIMER is recommended. Water thinnable, quick-drying and absolutely non-yellowing. When used on woods capable of swelling when exposed to water (e.g. beech), fine cracks and roughening may occur since AGLAIA WOOD IMPREGNATION PRIMER is a water-based product. Therefore, make samples first.

Aftertreatment and Care:

High traffic furniture and work tables may be thoroughly cleaned with an emery sponge from time to time, using AGLAIA BALSAM LACQUER THINNER. Aftertreatment with AGLAIA FURNITURE WAX avoiding thick layers of wax. Thoroughly remove old wax from raw, worn or damaged wood with AGLAIA BALSAM LACQUER THINNER, sand and retreat systematically. Partial mending will often be an option. For regular care, add AGLAIA SELF-GLOSSY WAX to the cleaning water (1 teaspoon in 1 l clear water).

For more information refer to our AGLAIA Special Care Instructions for Oiled and Waxed Floor Tiles, Cork and Parquet Floors.

Safety Instructions and Disposal:

► Hazard Class: Flammable (VbF [Flammable Liquids Regulation] A II!)

When applying, keep away from any ignition source, refrain from smoking and ensure proper ventilation.

Wear solvent-resistant gloves when applying with a cloth. Dispose of cloth in an airtight container because of flammability. Chemically sensitive and environmentally ill persons please pay attention to the full declaration. Keep out of reach of children. Do not dispose of organic care product into the sewage system. Disposal of product remainders according to legal regulations. Disposal of empty containers through resource collection points.

► Waste Code: Product and Product Remainers (European Waste Code): 080199 (Coatings).

It is our objective to provide, through this technical information, advice based on our skills and practical experience. Any instructions given are non-binding and do not release the user from his or her liability to check for product suitability and application methods him/herself with regard to the surface used. Technical modifications may result from product development. Upon publication of a revised or new version, these instructions will automatically lose their validity. The details contained in the EU Safety Data Sheets in their current form dictate liability for classification in terms of the Hazardous Substances Regulation, disposal etc.