

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**BEECK Quartz Paint**

Print date: 20.05.2015

Product code: FWB\_B26

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

BEECK Quartz Paint

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Interior silicate paint.

The product is to be used exclusively for the applications named in the technical data sheet or in the processing instructions.

**1.3. Details of the supplier of the safety data sheet**

Company name:	BEECK'SCHE FARBWERKE GmbH	
Street:	Neustadt 458	
Place:	D-84028 Landshut	
Telephone:	+49 (0) 7333 / 9607-11	Telefax: +49 (0) 7333 / 9607-10
e-mail:	info@beeck.com	
Contact person:	Ralf Rieks	Telephone: +49 (0) 7333 / 9607-14
e-mail:	Ralf.Rieks@beeck.com	
Internet:	www.beeck.com	
Responsible Department:	Factory Laichingen, Gottlieb-Daimler-Str. 4, D-89150 Laichingen Tel. +49(0)7333/9607-11 Fax: +49(0)7333/9607-10 Mo-Fr: 8.00 -16.00 hour	

**1.4. Emergency telephone number:** United Kingdom +44 870 600 626 / 0870 600 6266  
GBK Gefahrgut Büro GmbH  
+49(0)6132/84463

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

This mixture is not classified as hazardous according to Directive 1999/45/EC.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

**2.2. Label elements****Precautionary statements**

P102	Keep out of reach of children.
P262	Do not get in eyes, on skin, or on clothing.

**Special labelling of certain mixtures**

EUH210	Safety data sheet available on request.
--------	---

**2.3. Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Water: &gt;20 %

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## BEECK Quartz Paint

Print date: 20.05.2015

Product code: FWB\_B26

Page 2 of 8

### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
215-199-1	Silicic acid, potassium salt; Molar ratios > 3,2 (< 40%)	20 - < 25 %
1312-76-1		
	Calcium carbonate	5 - < 10 %
1317-65-3		
236-675-5	Titanium oxide	5 - < 10 %
13463-67-7		

Full text of R-, H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Show this safety data sheet to the doctor in attendance. Never give anything by mouth to an unconscious person. Lay the affected person down and keep him still; If unconscious, place the person in the recovery position.

#### After inhalation

Move to fresh air. Lay the affected person down, and keep her or him warm and calm. If symptoms persist, call a physician. In case of irregular breathing or respiratory arrest: Oxygen or artificial respiration, if needed.

#### After contact with skin

Wash contaminated skin areas thoroughly with soap and water. Remove soiled clothing. Do not use solvents or thinners. If skin irritation persists, call a physician.

#### After contact with eyes

Rinse with plenty of water immediately, also under the eyelids, for at least 15 minutes. Remove contact lenses, if applicable. Consult an ophthalmologist immediately.

#### After ingestion

Immediately give large quantities of water to drink.  
Do not induce vomiting. In the event of spontaneous nausea and unconsciousness, keep the head back and bring the patient into the recovery position.  
Lay the affected person down, and keep her or him warm and calm. Consult a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

nausea, vomiting, May cause eye/skin irritation.  
vomiting, cough, shortness of breath, abdominal pain

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment (decontamination and vital functions).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

The product itself does not burn. Use extinguishing measures that are appropriate to the environment.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**BEECK Quartz Paint**

Print date: 20.05.2015

Product code: FWB\_B26

Page 3 of 8

**Unsuitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture**

The release of the following substances is possible in a fire: carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), smoke, nitrogen oxides (NO<sub>x</sub>).

The inhalation of hazardous decomposition products may cause serious health damage.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus for fire fighting, if necessary.

**Additional information**

The combustion gases are partially condensed with the water used to extinguish the fire and end up as a contaminant in this water. Slaking water may have an alkaline effect.

Do not let product enter drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate personnel to a safe area. Provide good ventilation. Do not breathe in vapours and mist. Use personal protective equipment.

Slipping hazard due to leakage. Avoid bringing product in contact with the skin.

**6.2. Environmental precautions**

May not end up in waste water or open waters. Entry into rivers or surface water is to be prevented by the erection of barriers made of sand or earth or by other suitable barriers. Contact the responsible authority immediately if the product ends up in the soil, a body of water, or the sewer system.

**6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Dispose of as described in section 13. After cleaning, flush away traces with water.

**6.4. Reference to other sections**

See section 7, 8, 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide sufficient air exchange and/or exhaust in work rooms. Containers keep tightly closed. Avoid contact with skin and eyes.

The further treatment / removal of coatings by grinding, burning, etc. may create hazardous dust and/or vapour. Do not breathe vapours/dust.

When using, do not eat, drink, or smoke.

Suitable protective equipment: See section 8.

**Advice on protection against fire and explosion**

The product is not flammable.

The product is not explosive.

**Further information on handling**

Comply with the health and safety at work laws. Handle, store and transport in compliance with local regulations and in labelled containers that are suitable for this product.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Store in compliance with the local regulations. Store sealed in the original container.

Keep in a dry, cool place. Protect from freezing.

**Advice on storage compatibility**

Do not store near acids.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## BEECK Quartz Paint

Print date: 20.05.2015

Product code: FWB\_B26

Page 4 of 8

### Further information on storage conditions

Smoking in the storage rooms is forbidden. Entry by unauthorized individuals is forbidden.  
Keep at temperatures between 5°C and 25°C.  
Already opened containers should be closed thoroughly and should be stored upright in order to prevent leakage.

### 7.3. Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. This can be achieved by local or space exhaust. If this is not sufficient, in order to hold the solvent vapour concentration lower than the occupational exposure limit an approved respiratory protection apparatus must be worn.

#### Protective and hygiene measures

Avoid contact with skin and eyes. Do not breathe in vapours or spray mist. Remove and wash contaminated clothing before re-use. Do not eat, drink, smoke or take snuff at work. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal food stuffs.

#### Eye/face protection

Safety glasses at risk of splashing. Safety glasses with side-shields.  
Eye wash

#### Hand protection

Protective gloves  
The manufacturer recommends the following glove materials: PVC- or rubber gloves.  
Safety gloves should be selected for the actual conditions of use and in accordance with the instructions for use provided by the manufacturer.  
Preventive skin protection: skin protection cream.

#### Skin protection

Impervious clothing, boots, apron, protective gloves.  
Take off all contaminated clothing immediately. Wash contaminated skin areas thoroughly with soap and water.

#### Respiratory protection

When workers are facing concentrations above the exposure limit, they must use appropriate certified respirators. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.

#### Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### BEECK Quartz Paint

Print date: 20.05.2015

Product code: FWB\_B26

Page 5 of 8

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
 Colour: white resptv. tinted  
 Odour: mild

#### Test method

pH-Value (at 20 °C): 11 ISO 4316

#### Changes in the physical state

Melting point: No data available.  
 Initial boiling point and boiling range: No data available.  
 Sublimation point: No data available.  
 Softening point: No data available.  
 Flash point: not applicable

#### Explosive properties

No data available.

Lower explosion limits: No data available.  
 Upper explosion limits: No data available.

#### Auto-ignition temperature

Solid: No data available.  
 Decomposition temperature: No data available.  
 Vapour pressure: No data available.  
 Density: 1,54 g/cm<sup>3</sup>  
 Water solubility: No data available.

#### Solubility in other solvents

No data available.

Partition coefficient: No data available.

Viscosity / dynamic: 6500 mPa·s ISO 2555

Vapour density: No data available.

### 9.2. Other information

Solid content: No data available.

No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

Stable under proper storage and handling.

### 10.3. Possibility of hazardous reactions

No dangerous reactions occur under normal storage conditions and in normal use. Does not polymerize.

### 10.4. Conditions to avoid

None under normal use.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### BEECK Quartz Paint

Print date: 20.05.2015

Product code: FWB\_B26

Page 6 of 8

#### 10.5. Incompatible materials

strong oxidizers; strong acids

#### 10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

No data is available on the product itself.

Calcium carbonate  
LD50/oral/rat: 6450 mg/kg

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
1312-76-1	Silicic acid, potassium salt; Molar ratios > 3,2 (< 40%)				
	oral	LD50	> 2000 mg/kg	Rat	
1317-65-3	Calcium carbonate				
	oral	LD50	> 5000 mg/kg	rat	
13463-67-7	Titanium oxide				
	oral	LD50	>5000 mg/kg	rat	OECD 425
	dermal	LD50	>5000 mg/kg	rabbit	
	inhalative (4 h) aerosol	LC50	>6,8 mg/l	rat	

### SECTION 12: Ecological information

#### 12.1. Toxicity

No data is available on the product itself.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
1317-65-3	Calcium carbonate					
	Acute fish toxicity	LC50	>10000 mg/l	96 h	Rainbow trout (Oncorhynchus mykiss)	
	Acute algae toxicity	ErC50	>200 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50	>1000 mg/l	48 h	Daphnia magna	
13463-67-7	Titanium oxide					
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	16 mg/l		Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnia magna	OECD 202

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**BEECK Quartz Paint**

Print date: 20.05.2015

Product code: FWB\_B26

Page 7 of 8

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**Further information**

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste disposal number of waste from residues/unused products**

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

**Waste disposal number of used product**

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

**Contaminated packaging**

Suitable cleaning agents: Water resp. soapy water.

Packaging can be sent for recycling after being emptied and cleaned. If recycling is not practicable, dispose of in compliance with the official regulations and the Environmental Protection (Duty of Care) Regulations 1991.

**SECTION 14: Transport information****Land transport (ADR/RID)****Other applicable information (land transport)**

Not classified as dangerous regarding transport regulations.

**Inland waterways transport (ADN)****Other applicable information (inland waterways transport)**

Not classified as dangerous regarding transport regulations.

**Marine transport (IMDG)****Other applicable information (marine transport)**

Not classified as dangerous regarding transport regulations.

**Air transport (ICAO)****Other applicable information (air transport)**

Not classified as dangerous regarding transport regulations.

**14.6. Special precautions for user**

No data available.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No data available.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### BEECK Quartz Paint

Print date: 20.05.2015

Product code: FWB\_B26

Page 8 of 8

2004/42/EC (VOC):

The EU limit value for this product (product category: II. A a, Wb) in ready to use form is max 30 g/litre of VOC. The VOC content of this product in ready to use form is max 4 g/l

#### Additional information

No Substances of Very High Concern (SVHC) according REACH Article 57.

#### National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

n.a. = not applicable

n.d. = not determined

n.d.a. = no data available

#### Relevant H- and EUH-phrases (Number and full text)

EUH210 Safety data sheet available on request.

#### Further Information

The information is based on present levels of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The product is to be used exclusively for the applications named in the technical data sheet or in the processing instructions.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*